

INLINE
LAMINATION
MODULE

MATICA



ILM-LS/DS



MATICA



ILM-LS/-DS

INLINE LAMINATION MODULE

Responding to the growing demand for durable and secure, tamper-resistant cards, we have developed the most flexible and fastest lamination program on the market. The *EDIsecure*® Inline Lamination Modules help to meet the demanding needs of applications such as secure employee and visitor card, driving license or national ID. The compact *EDIsecure*® Inline Lamination Module ILM-LS offers an enormous flexibility to accommodate total cost, throughput requirements, and reliability. With applying *EDIsecure*® clear and secure laminates on the card, which includes patches with chip cut-out, the surface will be protected against physical damage and the card life extended. Custom design or generic holographic foils help to protect the cards against tampering. Due to the portrait mode lamination a very high lamination speed of 16 seconds per card (single side) can be achieved.

The ILM-LS can be combined easily for inline lamination with the *EDIsecure*® XID 8300 Retransfer Printer, simply attach the unit with the appropriate joining plate to the printer – that's it. Communicating via infrared interface, the lamination parameters for the various card materials are controlled by the printer driver. This allows the use of the laminator with all card materials, including PVC, Composite PVC, ABS, PET, and even Polycarbonate for longest card life. The laminator has a Kensington lock as well as an electronic security lock for the front door to secure the access to the supplies.

The laminator is also available as ILM-DS for simultaneous dual side lamination. Equipped with two lamination cartridges and separate temperature control of the upper and lower heat roller, even different laminates can be applied to the card at the same time. A special version of the ILM-DS can be combined with the *EDIsecure*® DCP 360+ Direct Card Printer and XID 93xx Retransfer Printers.

TECHNICAL SPECIFICATIONS

Lamination Method

Thermal transfer

Lamination Mode

Single-sided with ILM-LS

Double-sided (simultaneously) with ILM-DS

Lamination Speed

16 – 30* seconds per card (single- or double-sided)

Speed Settings

3 mm/s – 12 mm/s

Temperature Settings

90°C – 180°C adjustable in 5°C steps

Card Materials

PVC, Composite PVC, ABS, PET

and Polycarbonate Cards of ISO ID-1/CR-80 size, 85.60 x 53.98 mm

Card Thickness

0.76 mm

Dimensions

210 x 326 x 360 mm (WxDxH)

Weight

ILM-LS: 8.1 kg

ILM-DS: 9.0 kg

Power Supply

100/120 V and 220/240 V, 50/60 Hz

GOST-R, CE, and UL approved

Operating Environment

15°C to 30°C, 35% to 70% non-condensing humidity

MATICA

Matica Corp
sales@maticacorp.com



PH: 888.682.6567
WWW.COLORID.COM

maticacorp.com

Data subject to change without notice. All trademarks stated are the property of their respective owners. ILM-LS/DS_PD_2019_03_ENG_Letter