The SlimReel[™] System





The SlimReel[™] **System**

The SlimReel System* offers three different ways to carry a card in one convenient package.

This accessory can be used as a:

- Lanyard/badge reel combo
- Standalone lanyard
- Standalone badge reel

rtariaarene baage reer

* Patent pending

TWIST-FREE!

The SlimReel[™] System





SlimReel System - Stock Lanyard Specifications	
3/8" lanyard with color-matched clip-on SlimReel & breakaway.**	
Item#	Color
2138-8001	Black
2138-8002	Royal Blue (PMS 294)
2138-8006	Red (PMS 200C)
2138-8008	White
Lanyard Dimensions:	3/8" wide* x 36" long
Reel Cord Length:	28"
Reel Size:	1 1/4" x 1 11/16"
Label on Reel:	Multi-color flat or dome label
Label Size:	1" x 13/16"
Shipping Weight:	4.4 lb. per 100 pieces

STOCK COLOR OPTIONS:











- VERSATILE This three-in-one accessory can be utilized in different ways. Use it as the full lanyard/reel combination or detach the reel and use the lanyard and badge reel independently.
- CUSTOMIZABLE Both the lanyard and the badge reel can be customized for enhanced branding. Add a logo or text to a silkscreen, dye-sub, or woven lanyard, and add graphics to the reel with either a dome or flat label.
- CONVENIENT The lanyard and reel each feature the same snap clip, which was designed to make card carrying easy. It securely holds slotted ID cards, vinyl badge holders, and rigid badge holders.



^{**} SPECIAL WARNING FOR BREAKAWAY LANYARDS—Breakaway performance will vary and lanyards will not break away under all conditions. The male/female part pull force specification for round breakaways is 3-11 lb. under tested conditions per M-3-QA-0167. The male/female part pull force specification for flat standard breakaways is 4-10 lb. under test conditions per M-3-QA-0167. A full description of the M-3-QA-0167 test procedure can be provided upon request. Not recommended for use around moving objects or playgrounds.